



Pin	Description
1	input
5	+V _B
9	output
2.3.7.8	common

FEATURES >>

- Excellent linearity
- Extremely low noise
- Excellent return loss properties
- High gain
- High reliability

DESCRIPTION

Hybrid amplifier module operating over a frequency range of 40 to 1003 MHz at a voltage supply of +24V(DC) ,employing GaAs MMIC.

QUICK REFERENCE DATA

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
G _p	power gain	f=50 MHz	23.5	24	24.5	dB
G _p	power gain	f=1003MHz	25	26	26.5	dB
I _{tot}	total current consumption(DC)	V _B =24V	330	-	400	mA

LIMITING VALUES

In accordance with the Absolute Maximum Rating System

SYMBOL	PARAMETER	MIN.	MAX.	UNITS
V _i	RF input voltage	-	55	dBmV
T _{stg}	storage temperature	-40	+100	°C
T _{mb}	operating mounting base temperature	-20	+90	°C

CHARACTERISTICS

(Bandwidth 40 to 1003MHz; $T_{mb}=25^{\circ}C$, $V_B=24V$, $Z_S=Z_L=75\Omega$)

PART NUMBER			Egi10002524D1			
SYMBOL	PARAMETER	UNIT	MIN.	TYP.	MAX.	CONDITIONS
G_P	power gain	dB	23.5	24	24.5	$f = 50\text{MHz}$
SL	slope cable equivalent	dB	1	2	2.5	$f = 50$ to 1003 MHz
FL	flatness of frequency response	dB	-	-	± 0.5	$f = 40$ to 1003 MHz
S_{11} & S_{22}	Input & output return loss	dB	-	-	-16	$f = 40$ to 860 MHz
S_{11} & S_{22}	Input & output return loss	dB	-	-	-15	$f = 861$ to 1003 MHz
CTB	composite triple beat	dB	-	-	-60	110 channel
CSO	composite second order distortion	dB	-	-	-63	$V_o=50\text{dBmV}$ at 745.25MHz
X_{mod}	cross modulation	dB	-	-	-55	10dB tilted across the band
F	noise figure	dB	-	-	5	$f=860\text{ MHz}$
I_{tot}	total current consumption(DC)	mA	330	-	400	$V_B=+24V$

The module normally operates at $V_B=24V(\pm 0.5)$.

MODULE DIMENSIONS

